

Cont. sub. #12  
bringing] placing the component [and the] into a nest [into contact] having  
an asymmetrically shaped recess corresponding to the physically asymmetric marker on  
the component; and[,]

detecting whether the physically asymmetric marker on [said] the  
component mates with the asymmetrically shaped recess.

subcl. 5. (Amended) The method of claim 3, wherein said detecting [the alignment  
includes providing a sensor within the recess to distinguish] further comprises  
distinguishing when [the leads or] the component [are] is in [the] a predetermined  
alignment.

6. (Amended) The method of claim 5, wherein [providing a sensor includes  
providing a vacuum sensor] said detecting further comprises:  
creating a low pressure region in the recess; and  
sensing a pressure in the low pressure region.

7. (Amended) The method of claim 5, wherein [providing a sensor 10  
includes providing a contact sensor] said detecting further comprises sensing when a  
component contacts a surface of said recess.

8. (Amended) The method of claim 3, wherein said detecting [the alignment  
includes providing a receiver to detect] further comprises detecting whether the fiducial  
marker of the component mates with the asymmetrically shaped recess.

5hB2- 9. (Amended) The method of claim 8, wherein[:  
]detecting the alignment further [includes positioning an emitter to]  
comprises:  
[direct] directing a pattern of radiation [toward] above and parallel to the  
recess in the nest; [and,]  
[providing a receiver further includes providing a receiver in a position to  
receive emitted] receiving the radiation pattern that passes the recess;

Cont. Sub 15  
[indicative of] comparing the received radiation pattern to a predetermined radiation pattern; and

determining whether the fiducial marker is mated with the asymmetrical shaped recess.

Sub C17  
10. (Amended) The method of claim 1, [wherein providing a fiducial marker includes providing] further comprising forming a superficial asymmetric marker on said component.

11. (Amended) The method of claim 1, [wherein providing a fiducial marker] further [comprises] comprising forming [providing] multiple fiducial markers on said component.

12. The method of claim 1, wherein detecting the alignment further comprises detecting the fiducial marker visually.

Please add the following claims:

44. A method of placing a component having leads and an alignment indicating fiducial marker, comprising:

detecting the alignment of the fiducial marker on the component;  
comparing the detected fiducial alignment with a predetermined fiducial alignment; and

placing the component to a substrate when the detected fiducial alignment corresponds to the predetermined fiducial alignment.

45. The method of claim 44, wherein the fiducial marker corresponds to an alignment of the leads of the component.

46. The method of claim 44, wherein said detecting further comprises detecting an orientation of the fiducial marker.

conts  
A6

47. The method of claim 44, wherein said detecting further comprises detecting an orientation of the component.

48. The method of claim 44, wherein said placing the component further comprises placing a substrate in a component mounting area.

49. The method of claim 48, wherein said placing the component further comprises moving the component to the component mounting area.

50. The method of claim 44, further comprising discarding the component when the detected fiducial alignment does not correspond to the predetermined fiducial alignment.

51. The method of claim 44, further comprising halting operation of a component transfer apparatus when the detected fiducial alignment does not correspond to the predetermined fiducial alignment.

52. The method of claim 44, further comprising altering operation of a component transfer apparatus when the detected fiducial alignment does not correspond to the predetermined fiducial alignment.

53. The method of claim 44, further comprising continuously feeding components to the component feed assembly.

54. A method of placing a component having leads, comprising:  
placing the component in a nest having a surface and an asymmetric recess defined therein;

detecting the alignment of the component in the recess;  
comparing the detected alignment with a predetermined alignment; and  
placing the component to a substrate when the detected alignment corresponds to the predetermined alignment.

cont.  
AQ

AL

10  
 11  
 12  
 13  
 14  
 15  
 16  
 17  
 18  
 19  
 20  
 21  
 22  
 23  
 24  
 25  
 26  
 27  
 28  
 29  
 30  
 31  
 32  
 33  
 34  
 35  
 36  
 37  
 38  
 39  
 40  
 41  
 42  
 43  
 44  
 45  
 46  
 47  
 48  
 49  
 50  
 51  
 52  
 53  
 54  
 55  
 56  
 57  
 58  
 59  
 60  
 61  
 62  
 63  
 64  
 65  
 66  
 67  
 68  
 69  
 70  
 71  
 72  
 73  
 74  
 75  
 76  
 77  
 78  
 79  
 80  
 81  
 82  
 83  
 84  
 85  
 86  
 87  
 88  
 89  
 90  
 91  
 92  
 93  
 94  
 95  
 96  
 97  
 98  
 99  
 100  
 101  
 102  
 103  
 104  
 105  
 106  
 107  
 108  
 109  
 110  
 111  
 112  
 113  
 114  
 115  
 116  
 117  
 118  
 119  
 120  
 121  
 122  
 123  
 124  
 125  
 126  
 127  
 128  
 129  
 130  
 131  
 132  
 133  
 134  
 135  
 136  
 137  
 138  
 139  
 140  
 141  
 142  
 143  
 144  
 145  
 146  
 147  
 148  
 149  
 150  
 151  
 152  
 153  
 154  
 155  
 156  
 157  
 158  
 159  
 160  
 161  
 162  
 163  
 164  
 165  
 166  
 167  
 168  
 169  
 170  
 171  
 172  
 173  
 174  
 175  
 176  
 177  
 178  
 179  
 180  
 181  
 182  
 183  
 184  
 185  
 186  
 187  
 188  
 189  
 190  
 191  
 192  
 193  
 194  
 195  
 196  
 197  
 198  
 199  
 200  
 201  
 202  
 203  
 204  
 205  
 206  
 207  
 208  
 209  
 210  
 211  
 212  
 213  
 214  
 215  
 216  
 217  
 218  
 219  
 220  
 221  
 222  
 223  
 224  
 225  
 226  
 227  
 228  
 229  
 230  
 231  
 232  
 233  
 234  
 235  
 236  
 237  
 238  
 239  
 240  
 241  
 242  
 243  
 244  
 245  
 246  
 247  
 248  
 249  
 250  
 251  
 252  
 253  
 254  
 255  
 256  
 257  
 258  
 259  
 260  
 261  
 262  
 263  
 264  
 265  
 266  
 267  
 268  
 269  
 270  
 271  
 272  
 273  
 274  
 275  
 276  
 277  
 278  
 279  
 280  
 281  
 282  
 283  
 284  
 285  
 286  
 287  
 288  
 289  
 290  
 291  
 292  
 293  
 294  
 295  
 296  
 297  
 298  
 299  
 300  
 301  
 302  
 303  
 304  
 305  
 306  
 307  
 308  
 309  
 310  
 311  
 312  
 313  
 314  
 315  
 316  
 317  
 318  
 319  
 320  
 321  
 322  
 323  
 324  
 325  
 326  
 327  
 328  
 329  
 330  
 331  
 332  
 333  
 334  
 335  
 336  
 337  
 338  
 339  
 340  
 341  
 342  
 343  
 344  
 345  
 346  
 347  
 348  
 349  
 350  
 351  
 352  
 353  
 354  
 355  
 356  
 357  
 358  
 359  
 360  
 361  
 362  
 363  
 364  
 365  
 366  
 367  
 368  
 369  
 370  
 371  
 372  
 373  
 374  
 375  
 376  
 377  
 378  
 379  
 380  
 381  
 382  
 383  
 384  
 385  
 386  
 387  
 388  
 389  
 390  
 391  
 392  
 393  
 394  
 395  
 396  
 397  
 398  
 399  
 400  
 401  
 402  
 403  
 404  
 405  
 406  
 407  
 408  
 409  
 410  
 411  
 412  
 413  
 414  
 415  
 416  
 417  
 418  
 419  
 420  
 421  
 422  
 423  
 424  
 425  
 426  
 427  
 428  
 429  
 430  
 431  
 432  
 433  
 434  
 435  
 436  
 437  
 438  
 439  
 440  
 441  
 442  
 443  
 444  
 445  
 446  
 447  
 448  
 449  
 450  
 451  
 452  
 453  
 454  
 455  
 456  
 457  
 458  
 459  
 460  
 461  
 462  
 463  
 464  
 465  
 466  
 467  
 468  
 469  
 470  
 471  
 472  
 473  
 474  
 475  
 476  
 477  
 478  
 479  
 480  
 481  
 482  
 483  
 484  
 485  
 486  
 487  
 488  
 489  
 490  
 491  
 492  
 493  
 494  
 495  
 496  
 497  
 498  
 499  
 500  
 501  
 502  
 503  
 504  
 505  
 506  
 507  
 508  
 509  
 510  
 511  
 512  
 513  
 514  
 515  
 516  
 517  
 518  
 519  
 520  
 521  
 522  
 523  
 524  
 525  
 526  
 527  
 528  
 529  
 530  
 531  
 532

1000  
 900  
 800  
 700  
 600  
 500  
 400  
 300  
 200  
 100  
 0

B

ected fi



onent to  
d fiducia

Sub B3-  
the co

63. The  
determining whether

63.  
determining v

5. Sub 64. The method of claim 61, wherein said forming a fiducial marker shape includes forming a beveled edge on the component.

65. A method of placing a component having leads and an alignment indicating fiducial marker, comprising:

detecting the alignment of the fiducial marker on the component;  
comparing the detected fiducial alignment with a predetermined fiducial alignment;

providing an alignment signal; and  
placing the component to a substrate when the detected fiducial alignment corresponds to the predetermined fiducial alignment.

66. The method of claim 65, wherein said providing an alignment signal further comprises prompting an operator.

67. The method of claim 65, further comprising providing the alignment signal to a pick and place machine.

68. The method of claim 65, wherein the alignment signal corresponds to the presence or absence of a portion of a component extending beyond the nest surface.

69. The method of claim 65, wherein the alignment signal corresponds to whether the component is properly aligned in a recess of a nest.

70. The method of claim 65, further comprising affecting a control scheme in response to the alignment signal.

71. A method of placing a component having leads and an alignment indicating fiducial marker, comprising:

directing a pattern of radiation across a nest having an asymmetric recess corresponding to an asymmetric shape of the component;

sensing the radiation pattern passing across the nest;

detecting the alignment of the fiducial marker on the component;

comparing the detected fiducial alignment with a predetermined fiducial alignment; and

placing the component to a substrate when the detected fiducial alignment corresponds to the predetermined fiducial alignment.

72. The method of claim 71, wherein said directing further comprises disrupting the radiation pattern when a component is misaligned in the nest recess.

73. The method of claim 71, wherein said comparing further comprises comparing the radiation pattern passing across the nest to a known radiation pattern.

74. A method of placing a component having leads and an alignment indicating fiducial marker, comprising:

detecting the alignment of the fiducial marker on the component;

comparing the detected fiducial alignment with a predetermined fiducial alignment;

determining a component alignment from said comparison of the fiducial alignment with the predetermined alignment; and

placing the component to a substrate when the detected fiducial alignment corresponds to the predetermined fiducial alignment.

75. The method of claim 74, further comprising calculating a component position offset.

76. The method of claim 75, further comprising:

moving a nest from a first position into alignment with the component;

placing the component in the nest; and

returning the nest to the first position.

77. A method of placing a component having leads and an alignment indicating fiducial marker, comprising:

detecting the alignment of the fiducial marker on the component;

comparing the detected fiducial alignment with a predetermined fiducial

alignment;

causing a pick and place machine to pick the component; and  
placing the component to a substrate when the detected fiducial alignment  
corresponds to the predetermined fiducial alignment.

78. The method of claim 77, further comprising aligning the component when  
the detected fiducial alignment does not correspond to the predetermined fiducial  
alignment.

79. A method of placing a component having leads to a substrate, comprising:  
detecting alignment of a fiducial marker on the component; and  
placing the component to the substrate when the detected fiducial alignment  
corresponds to a predetermined fiducial alignment.

80. A method of placing a component having leads to a substrate, comprising:  
comparing an alignment of a fiducial marker on a component with a  
predetermined fiducial alignment; and  
placing the component to the substrate when the detected fiducial  
alignment corresponds to the predetermined fiducial alignment.

81. The method of claim 80, further comprising aligning the fiducial marker  
on the component with the predetermined fiducial alignment.

82. A method of placing a component having leads and an alignment indicating  
fiducial marker, comprising:

detecting the alignment of the fiducial marker on the component;  
comparing the detected fiducial alignment with a predetermined fiducial  
alignment;

aligning the component so that the fiducial marker corresponds to the  
predetermined fiducial alignment; and

placing the component to the substrate when the detected fiducial alignment  
corresponds to the predetermined fiducial alignment.--